



## **S-180 PUMPER MODEL 2208**

AVAILABLE FOR IMMEDIATE DELIVERY



## Chassis

- Freightliner M2-106
- Seating Capacity: 5
- Cummins L9 350EV HP
- Allison 3000 EVS Transmission
- Front: 14,600 lbs. Rear: 27,000 lbs.
- 18" Front Bumper Extension
- 235" Wheelbase
- 50 Gallon Fuel Tank
- Dual 25" StutterTone Air Horns
- 320 Amp Leece Neville Alternator
- (3) Group31 Maintenance Free Batteries
- 6 Gallon DEF Tank
- Double Frame
- Michelin Tires
- Alcoa Aluminum Dura-Brite Rims
- AM/FM Radio with Bluetooth, USB and Aux
- NFPA Seat Belt Display
- NFPA Vehicle Data Recorder

## **Pump and Plumbing**

- Hale DSD 1500 GPM Pump
- Trident Air Primer
- Class1 TPG+ Pressure Governor
- UPF 1000 Gallon Poly Water Tank
- 20 Gallon Foam Cell
- (1) 2.5" Left Side Auxiliary Inlet
- (1) 2.5" Right Side Auxiliary Inlet
- (1) 2.5" Left Side Discharge
- (1) 2.5" Right Side Discharge
- (1) 3" Right Side Discharge w/4" Storz
- (1) 2.5" Left Rear Discharge
- (1) 3" Deck Gun Discharge terminates pipe thread
- (2) 1.75" Crosslays
- (1) 1.5" Front Bumper Discharge

## **Body**

- 168" Formed Aluminum Body
- Vibra-Torque Body Mounting System
- ROM Series IV Roll-up Doors
- Full Height w/ Right Split Depth Compartments & Left Full Depth
- Ladders (Duo Safety, 24', 14', 10' Attic)
- Left Side SCBA storage for (8) Cylinders
- Double "V" trough for two 6" PVC Hose
- 19" Hosebed Riser Side Walls
- 22 oz Hypalon Hose Bed Cover
- Eck Anti-Corrosion Process
- SparLiner Compartment Finish
- OnScene Access LED Compartment Lighting
- Whelen M6 Series LED Lighting Package
- Whelen M9 Side & Rear Scene Lights





